




SDS FULLY AUTOMATED MOBILE FILL AND DE-AIRING STATION

The **SDS Mobile Station** is the most compact versatile Oil De-Airing station ever built. It is the only portable automated fill station on the market. It can be used as a portable single pulser oil filling station or in a permanent setup it can fill up to 4 pulsers at the same time. No assembly is required, and the setup time is under a minute. The process is fully automated and does not require supervision.

The **SDS Mobile Station** is a two-tank design unit. The oil is being circulated through the pulser by circulating the oil from one tank to the other and back. The two-tank system allows for faster de-airing of the oil.



The **SDS Mobile Station** has every capability to maximize performance and optimization which is the key to reducing costs and minimizing downtime in a competitive market. The **SDS Mobile Station** will give you the reliability that clients demand.





SDS MOBILE STATION SPECIFICATIONS

SDS Mobile Station Specifications		
Cabinet Size / Portable or Wall Mount	Inches	24 x 24
	mm	610 x 610
Number of Pulsers at one time	Capacity	4 Per cycle
	Minimum	1 Per Cycle
Tank Size	Inches	18
	OD Inches	4
Quick Disconnect Couplers	Type	Brass check valve
Flow Direction	Selectable	Reversible
Solenoid Valves	Automated	
Optic fluid level sensors	Automated	
Single fill drain port		
Manual or auto mode	Selectable	No staff monitoring Req
UNIT IS AVAILABLE WITH CUSTOM OPTIONS		Low vibration De-Airing
		Automated Pulsar turning

